

# Product datasheet

Specifications



## TeSys Vario - switch disconnector - 32 A - back of enclosure

VVD1

**Price: 1,000.14 ZAR**

### Main

Range	TeSys
Product Name	TeSys VARIO
Device Short Name	VVD
Device Application	Preventive maintenance
Product Type	Switch disconnector

### Complementary

Device Composition	Handle Switch
Mounting Support	Switch: symmetrical rail Switch: plate
Mounting Method	By clips for switch By screws for switch
Performance Level	High performance
Number Of Poles	3P
Contact Type And Composition	3 NO
[Ue] Iec Rated Operational Voltage	690 V AC 50/60 Hz
Iec Rated Operational Power In W	11 kW at 500 V (AC-23A) 15 kW at 690 V (AC-23A) 7.5 kW at 500 V (AC-3) 7.5 kW at 690 V (AC-3) 1.5 kW at 230...240 V (AC-3) 5.5 kW at 230...240 V (AC-23A) 11 kW at 400...415 V (AC-23A) 7.5 kW at 400...415 V (AC-3)
[Ie] Rated Operational Current	21.8 A AC-23 Ue: 400 V
[Ith] Conventional Free Air Thermal Current	32 A
[Ithe] Conventional Enclosed Thermal Current	25 A
Making Capacity ( I Rms)	320 A at 400 V AC-21A 320 A at 400 V AC-22A 320 A at 400 V AC-23A
Breaking Capacity	250 A at 400 V (AC-21A) 250 A at 400 V (AC-22A) 250 A at 400 V (AC-23A)
Rated Conditional Short Circuit Current	10 kA at 400 V - associated fuse 35 A aM 10 kA at 400 V - associated fuse 35 A gG
[Icm] Rated Short Circuit Making Capacity	1 kA at 400 V at Ipeak
[Icw] Rated Short Time Withstand Current	384 A at 400 V duration: 1 s

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

<b>[Uimp] Rated Impulse Withstand Voltage</b>	8 kV
<b>Suitability For Isolation</b>	Yes
<b>Network Type</b>	DC AC
<b>Intermittent Duty Class</b>	30
<b>Control Type</b>	Rotary handle
<b>Rotary Handle Mounting Style</b>	Direct
<b>Handle Color</b>	Black
<b>Handle Front Plate Color</b>	Black
<b>Rotary Handle Padlocking</b>	Without
<b>Marking</b>	0 - 1
<b>Mechanical Durability</b>	100000 cycles
<b>Electrical Durability</b>	100000 cycles AC-21 30000 cycles DC-1...5
<b>lec Terminal Connection</b>	Power circuit: screw clamp terminals10 mm <sup>2</sup> - solid Power circuit: screw clamp terminals6 mm <sup>2</sup> - flexible - with cable end
<b>Tightening Torque</b>	Power circuit: 2.1 N.m - on screw clamp terminals
<b>Base Dimension</b>	45 x 45 mm
<b>Height</b>	74 mm
<b>Width</b>	55 mm
<b>Depth</b>	106 mm
<b>Product Weight</b>	0.25 kg

## Environment

<b>Standards</b>	IEC 60947-3
<b>Product Certifications</b>	UL GL CSA UKCA
<b>Degree Of Protection</b>	IP65 IP65 conforming to IEC 60529
<b>Protective Treatment</b>	TC
<b>Mechanical Robustness</b>	Vibrations 10...150 Hz (1 gn) conforming to IEC 60068-2-6 Shocks 11 ms (30 Gn) conforming to IEC 60068-2-27
<b>Ambient Air Temperature For Operation</b>	-20...50 °C
<b>Fire Resistance</b>	960 °C conforming to IEC 60695-2-1
<b>Compatibility Code</b>	Main switch disconnecter

## Packing Units

<b>Unit Type Of Package 1</b>	PCE
<b>Number Of Units In Package 1</b>	1
<b>Package 1 Height</b>	8.000 cm
<b>Package 1 Width</b>	8.500 cm
<b>Package 1 Length</b>	12.000 cm
<b>Package 1 Weight</b>	184.000 g

<b>Unit Type Of Package 2</b>	S01
<b>Number Of Units In Package 2</b>	4
<b>Package 2 Height</b>	15.000 cm
<b>Package 2 Width</b>	15.000 cm
<b>Package 2 Length</b>	40.000 cm
<b>Package 2 Weight</b>	869.000 g
<b>Unit Type Of Package 3</b>	P06
<b>Number Of Units In Package 3</b>	128
<b>Package 3 Height</b>	75.000 cm
<b>Package 3 Width</b>	80.000 cm
<b>Package 3 Length</b>	60.000 cm
<b>Package 3 Weight</b>	35.808 kg

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

✓ Pvc Free

✓ Halogen Free Product

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile No need of specific recycling operations