

Product datasheet

Specifications



encoder interface card with RS422
compatible differential outputs - 5 V
DC

VW3A3401

Price: 3,834.60 ZAR

Main

Range Of Product	Altivar
Product Or Component Type	Encoder interface card
Range Compatibility	Altivar Lift Altivar 61 Altivar 71Q Altivar 71 Altivar 61Q
Discrete Output Type	Differential
Communication Port Protocol	RS422
[Us] Rated Supply Voltage	5 V DC (voltage limits: 5...5.5 V)
Number Of Pulses Per Revolution	10000 for ATV71H.....383 5000 for all ATV61 drives 5000 for ATV71H...M3 5000 for ATV71H...M3X 5000 for ATV71H...N4

Complementary

Maximum Supply Current	0.2 A
Protection Type	Short-circuit protection Overload protection
Maximum Cable Distance Between Devices	50 m
Maximum Operating Frequency	300 kHz
Input Signal	A B Compliment of A Compliment of B
Input Impedance	440 Ohm
Electrical Connection	Terminal, connection capacity: 0.2 mm ² (AWG 24) <25 m cable length, encoder, 100 mA at 4.5 V Terminal, connection capacity: 0.5 mm ² (AWG 20) <25 m cable length, encoder, 200 mA at 4.5 V Terminal, connection capacity: 0.5 mm ² (AWG 20) <50 m cable length, encoder, 100 mA at 4.5 V Terminal, connection capacity: 0.75 mm ² (AWG 18) <50 m cable length, encoder, 200 mA at 4.5 V
Net Weight	0.2 kg

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	7.500 cm

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Package 1 Width	17.000 cm
Package 1 Length	23.000 cm
Package 1 Weight	142.000 g
Unit Type Of Package 2	S03
Number Of Units In Package 2	7
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	1.479 kg

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Mercury Free

RoHS Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu RoHS Directive Pro-active compliance (Product out of EU RoHS legal scope)

China RoHS Regulation [China RoHS declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile No need of specific recycling operations