

Product datasheet

Specifications



Multisound siren. Harmony XVS.
Multi sound white. 0...105 dB. 43
tones. 8 channels. 120 V AC

XVS14GMW

Price: 8,103.41 ZAR

Main

Range Of Product	Harmony XVS
Product Or Component Type	Multisound siren
Device Short Name	XVS

Complementary

Colour	White
Material	PC (polycarbonate): back cover PC (polycarbonate)/ABS (acrylonitrile butadiene-styrene): front PC (polycarbonate)/ABS (acrylonitrile butadiene-styrene): back
Net Weight	1.2 kg
Marking	CE
Mounting Support	Bracket
Fixing Mode	3 holes Ø 9 mm
[Uimp] Rated Impulse Withstand Voltage	4 kV
Current Consumption	100 mA at 120 V
Electrical Connection	Cable: 6.5...8.5 mm, 0.33 mm² / AWG 22 (signalling circuit) Cable: 6.5...8.5 mm, 0.52 mm² / AWG 20 (power circuit)
Width	140 mm
Height	114 mm
Depth	223 mm

Environment

Signalling Type	43 tones siren
Standards	IEC 61000-6-2 IEC 61000-6-3 IEC 60947 EN 60947-5
Product Certifications	UL
Protective Treatment	TC
Ambient Air Temperature For Storage	-35...70 °C
Ambient Air Temperature For Operation	-10...50 °C
Overvoltage Category	Class II conforming to IEC 61140
Ip Degree Of Protection	IP53 conforming to IEC 60529
[Us] Rated Supply Voltage	120 V AC

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Noise Level	0...105 dB (continuous or intermittent tone) at 1 m
-------------	---

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	15.49 cm
Package 1 Width	16 cm
Package 1 Length	27.94 cm
Package 1 Weight	1.56 kg
Unit Type Of Package 2	S04
Number Of Units In Package 2	6
Package 2 Height	30 cm
Package 2 Width	40 cm
Package 2 Length	60 cm
Package 2 Weight	10.856 kg
Unit Type Of Package 3	PAL
Number Of Units In Package 3	24
Package 3 Height	60 cm
Package 3 Width	80 cm
Package 3 Length	24 cm
Package 3 Weight	38.064 kg

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency

Well-being performance

✓	Mercury Free	
✓	Rohs Exemption Information	Yes
Eu Rohs Directive		Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation		China RoHS declaration
Environmental Disclosure		Product Environmental Profile
Circularity Profile		End of Life Information

Dimensions Drawings

Siren

Dimensions

