

Product datasheet

Specifications



Harmony XVS. Editable voice alarms. black. mounting 96 mm DIN rail. PNP. 12...24V DC

XVSV9BBP

Price: 5,516.41 ZAR

Main

Range Of Product	Harmony XVS
Product Or Component Type	Editable electronic alarm
Beacon Or Indicator Bank Unit Type	Sound unit
Device Short Name	XVSV

Complementary

Colour	Dark grey
Input Type	Bit: 6 channel input Binary: 63 channel input
Assembly Style	Ready assembled
Material	PC (polycarbonate): body PC (polycarbonate): back cover TPE (thermoplastic elastomer): front panel NBR (nitrile butadiene rubber)
Marking	CE
Overvoltage Category	Class II conforming to IEC 61140
Mounting Support	96 mm DIN rail
[Us] Rated Supply Voltage	12...24 V DC
[Ue] Rated Operational Voltage	10...30 V DC
[Ui] Rated Insulation Voltage	250 V
Inrush Current	30 A
Associated Fuse Rating	1 A
[Uimp] Rated Impulse Withstand Voltage	2.5 kV conforming to IEC 60947-1
Power Consumption In W	3.8 W
Current Consumption	160 mA at 24 V DC
Clamping Connection Capacity	<= 1 x 1.5 mm²
Device Application	Printing Packaging Subway
Mounting Diamete	105 mm
Width	105 mm
Height	105 mm
Depth	50.1 mm
Net Weight	0.268 kg

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Discrete Output Type	PNP
Signalling Type	Adjustable vocal sound
Standards	IEC 60947-5-1
Protective Treatment	TC
Ambient Air Temperature For Storage	-20...60 °C
Ambient Air Temperature For Operation	-10...55 °C
Pollution Degree	2
Relative Humidity	35...85 % without condensation
Vibration Resistance	7 gn
Ip Degree Of Protection	Panel mounted: IP65 conforming to IEC 60529 Wall mounted: IP20
Noise Level	0...97 dB (stop or suppress) at 1 m

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	10.5 cm
Package 1 Width	5 cm
Package 1 Length	10.5 cm
Package 1 Weight	268 g

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓

Mercury Free

✓

Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Pro-active compliance (Product out of EU RoHS legal scope)

China Rohs Regulation

[China RoHS declaration](#)

Environmental Disclosure


[Product Environmental Profile](#)

Circularity Profile

[End of Life Information](#)

Dimensions Drawings


Dimensions



(t) : Waterproof rubber (1.6 mm / 0.06 in.)

Mounting and Clearance


Panel Cut Dimensions



(1) Installation panel

A	B	C
92 +0.6/0 mm (3.62 +0.0236/0 in.)	92 +0.6/0 mm (3.62 +0.0236/0 in.)	1...4 mm (0.04...0.15 in.)


Wall Mount Dimensions



(1) Installation panel

Connections and Schema

Wiring Diagram



- (1) Green
- (2) Yellow
- (3) Brown
- (4) Blue
- (5) Purple
- (6) Gray
- (7) White
- (8) Black
- (9) Red
- (10) Fuse (Rated current:1 A)