

# Product datasheet

Specifications



Head for key selector switch.  
Harmony XB4. Ø22 mm. 2 position  
specific

ZB4BG2K1323A

⚠ Discontinued on: 15 Jun 2023

⚠ Discontinued

## Main

|                               |                              |
|-------------------------------|------------------------------|
| Range Of Product              | Harmony XB4                  |
| Product Or Component Type     | Head for key selector switch |
| Device Short Name             | ZB4                          |
| Mounting Diamete              | 22 mm                        |
| Head Type                     | Standard                     |
| Sale Per Indivisible Quantity | 1                            |
| Shape Of Signaling Unit Head  | Round                        |
| Operator Profile              | key switch                   |
| Operator Position Information | 2 positions 90°              |
| Type Of Keylock               | Special key                  |

## Complementary

|                                    |                                       |
|------------------------------------|---------------------------------------|
| Resistance To High Pressure Washer | 7000000 Pa at 55 °C, distance : 0.1 m |
| Mechanical Durability              | 1000000 cycles                        |
| Device Presentation                | Basic element                         |

## Environment

|                                       |                                                                                                                                                                                |
|---------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Protective Treatment                  | TH                                                                                                                                                                             |
| Ambient Air Temperature For Storage   | -40...70 °C                                                                                                                                                                    |
| Ambient Air Temperature For Operation | -40...70 °C                                                                                                                                                                    |
| Overvoltage Category                  | Class I conforming to IEC 60536                                                                                                                                                |
| Ip Degree Of Protection               | IP66 conforming to IEC 60529<br>IP67<br>IP69<br>IP69K                                                                                                                          |
| Nema Degree Of Protection             | NEMA 13                                                                                                                                                                        |
| Vibration Resistance                  | 5 gn (f= 2...500 Hz) conforming to IEC 60068-2-6                                                                                                                               |
| Shock Resistance                      | 30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC 60068-2-27<br>50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27 |

## Packing Units

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                              |        |
|------------------------------|--------|
| Unit Type Of Package 1       | PCE    |
| Number Of Units In Package 1 | 1      |
| Package 1 Height             | 8.6 cm |
| Package 1 Width              | 3.3 cm |
| Package 1 Length             | 5.2 cm |
| Package 1 Weight             | 98.0 g |

Sustainability



**Green Premium™ label** is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency   RoHS/REACH

## Well-being performance



Mercury Free



Rohs Exemption Information

Yes

## Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Pro-active compliance (Product out of EU RoHS legal scope)

China Rohs Regulation

[China RoHS declaration](#)

Environmental Disclosure

[Product Environmental Profile](#)

Circularity Profile

[End of Life Information](#)