

Product datasheet

Specifications



Rack PDU, Switched, 2U, 32A, 230V, (16)C13



AP7922B

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Colour	Black
product or component type	PDU
PDU type	Switched
Cord length	3.05 m
Number of cables	1
Provided equipment	Documentation CD Installation guide Rack mounting brackets

Complementary

Input Voltage	200 V 208 V 230 V
Height	8.9 cm
Width	44.5 cm
Output Voltage	230 V
Depth	11.4 cm
net weight	4.5 kg
mounting location	Front Rear
Mounting preference	No preference
Input Plug Type	IEC 60309 32 A 2P + E
mounting mode	Rack-mounted
Rack units	2U
Mounting position	Horizontal
Permissible voltage	220...240 V
Input current limits	32 A
Load capacity	7360 VA
Network frequency	50/60 Hz
Outlet type and quantity	16 IEC 60320 C13

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Product certifications	CE GOST IRAM MIC VDE
Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3
ambient air temperature for operation	0...45 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.0000000000...15240.0000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14 cm
Package 1 Width	36.8 cm
Package 1 Length	50.8 cm
Package 1 Weight	6.55 kg

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

- 

 Energy Efficient Product
- 

 Take-Back Program Available

Well-being performance

- 

 Mercury Free
- 

 Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACH Declaration
Eu Rohs Directive	Compliant with Exemptions
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Image of product / Alternate images

Alternative

