



PRODUCT-DETAILS

XT4N 160 TMD 20-300 4p F F

XT4N 160 TMD 20-300 4p F F



General Information	
Extended Product Type	XT4N 160 TMD 20-300 4p F F
Product ID	1SDA068094R1
EAN	8015644695842
Catalog Description	XT4N 160 TMD 20-300 4p F F
Long Description	C.BREAKER TMAX XT4N 160 FIXED FOUR-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMD R 20-300 A

ABB EcoSolutions	
ABB EcoSolutions	Yes
Circular Design	Design for Closing Resource Loops - Standard EN45555 - 56.30 %
Principles Recyclability Rate	
End of Life Instructions	9AKK108468A2351
Environmental Product Declaration - EPD	9AKK108469A1857 9AKK108468A1892
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available

Material Compliance		
REACH Declaration		9AKK108466A1425
RoHS Information		9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019	
Conflict Minerals Reporting Template (CMRT)		9AKK108467A5658
Toxic Substances Control Act - TSCA		9AKK108467A8326

Environmental		
Environmental Information		9AKK108467A6707

Ordering		
Order Code US and Canada		XT4NE4020AFF000XXX
E-Number (Norway)		4380079
EAN		8015644695842
Minimum Order Quantity		1 piece
Customs Tariff Number		85362090

Dimensions		
Product Net Width		140 mm
Product Net Height		160 mm
Product Net Depth / Length		82.5 mm
Product Net Weight		3.5 kg

Container Information		
Package Level 1 Units		box 1 piece
Package Level 1 Width		145 mm
Package Level 1 Height		210 mm
Package Level 1 Depth / Length		168 mm
Package Level 1 Gross Weight		3.5 kg
Package Level 1 EAN		8015644695842

Additional Information		
Circuit Breaker Type to be Associated		Power Distribution
Product Main Type		SACE Tmax XT
Product Name		Moulded Case Circuit Breaker
Product Type		Automatic Circuit Breaker
Version		F
CAD Dimensional		1SDH001295R0677

Drawing

Technical	
Connecting Capacity Main Circuit	Busbar 85..200 mm²
Current Type	AC/DC
Electrical Durability	120 cycles per hour 8000 cycle
Mechanical Durability	240 cycles per hour 25000 cycle
Number of Poles	4P
Opening Time	CB with SOR 15 ms CB with UVR 15 ms
Order Multiple	1 piece
Power Loss	at Rated Operating Conditions per Pole 2.6 W
Rated Current (I _N)	20 A
Rated Frequency (f)	50 / 60 Hz
Rated Impulse Withstand Voltage (U _{imp})	8 kV
Rated Instantaneous Short-Circuit Current Setting (I _i)	300 A
Rated Insulation Voltage (U _i)	1000 V
Rated Operational Voltage	690 V AC 750 V DC
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(220 V AC) 65 kA (230 V AC) 65 kA (240 V AC) 65 kA (380 V AC) 36 kA (415 V AC) 36 kA (440 V AC) 36 kA (500 V AC) 30 kA (525 V AC) 20 kA (690 V AC) 10 kA (250 V DC) 2 Poles in Series 36 kA (500 V DC) 2 Poles in Series 36 kA (500 V DC) 3 Poles in Series 36 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})	(220 V AC) 65 kA (230 V AC) 65 kA (240 V AC) 65 kA (380 V AC) 36 kA (415 V AC) 36 kA (440 V AC) 36 kA (500 V AC) 30 kA (525 V AC) 20 kA (690 V AC) 10 kA (250 V DC) 2 Poles in Series 36 kA (500 V DC) 2 Poles in Series 36 kA (500 V DC) 3 Poles in Series 36 kA
Rated Uninterrupted Current (I _u)	160 A
Rated Voltage (U _r)	690 V
Recommended Screw Driver	Main Circuit M8
Release	TMD
Release Type	TM
Setting Range	14...20 A
Short-Circuit Performance Level	N

Standards	IEC60947-2
Sub-type	XT4
Terminal Connection Type	Front
Terminal Type	Bolt
Tightening Torque	8 N·m

Certificates and Declarations

ATEX Certificate	No certification needed
Data Sheet, Technical Information	1SDC210100D0206 1SDC210099D0206
Declaration of Conformity - CE	9AKK106713A5529
GL Certificate	1SDL000163R0095
LR Certificate	1SDL000163R0100
UL Certificate	No certification needed
VDE Certificate	No certification needed
Dimension Diagram	1SDH000722R0100
Mechanical Drawings	1SDH000722R0100
Wiring Diagram	1SDM000068R0001
Instructions and Manuals	1SDH000722R0001

Classifications

ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
UNSPSC	39120000
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

