



DCP-96 VAC

DCP-96 VAC, Three-phase digital voltmeter

Code: M22410.

- > Scale: 3 x 230 / 400V
- > System: AC
- > Paramètre: V, Hz
- > Mounting: Pannel
- > Modules: 96 x 96

Specifications

AC power supply

Installation category	CAT III 300 V
Consumption	1 ... 4 VA
Frequency	50/60 Hz
Nominal voltage	80 ... 270 Vac

DC power supply

Installation category	CAT III 300 V
Consumption	0.5 ... 0.7 W
Nominal voltage	80...270 Vdc

Mechanical characteristics

Size (mm) width x height x depth	96 x 96 x 41.5 (mm)
Envelope	Polycarbonate + ABS
Weight (kg)	0,3

Environmental characteristics

Protection class	Front: IP54, Rear: IP20
Relative humidity (without condensation)	≤ 95%
Storage temperature	-40... +85 °C
Working temperature	-25 ... +70°C

Voltage measurement circuit

Installation category	CAT III 300 V
Consumption	< 0.2 VA (por fase)
Sampling frequency	45...65 Hz
Input impedance	> 1.7 MΩ
Voltage measuring range	45 ... 65 Hz
Nominal voltage	100...277 V~ Ph-N (± 8%)
Maximum permanent measurement voltage	1.2 Un continuous, 2 Un instantaneous (1 min)

Standards

Electrical safety, Maximum height (m)	2000
Electrical safety, Installation category	CAT III 300 V



DCP-96 VAC

Panel-mounted digital instruments

Code: M22410.

Electrical safety, Contamination level/class	Pollution resistance 2
Standards	IEC 61010-1, IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-8, IEC 61000-4-11

User interface

Keyboard	3 keys
Display type	LCD

Measurement accuracy

Frequency measurement	± 0.01 Hz
Phase voltage measurement	0.2 % (± 1 digit)

DCP-96

CODE	TYPE	Scale	System	Paramètre	Modules
M22410.	DCP-96 VAC	3 x 230 / 400V	AC	V, Hz	96 x 96
M22450.	DCP-96 AAC	.../5A, .../1A	AC	A,Hz	96 x 96



DCP-96 VAC

Panel-mounted digital instruments

Code: M22410.

Connections

