

universal busbar support (01485)



Description

Part No.: 01485
universal busbar support
4-pole with internal screw holes
for busbars 12, 15, 20, 25, 30 x 5, 10

System

60Classic

Product group 06

Subgroup 12

pack size 10

EAN 4021267014858

Advantages of the product

With internal screw holes

can also be used as centre support

With the 4th pole, the width of the busbar can be set independent of L1, L2 and L3.

catalog page 2020 : 3.1

eCl@ss 6.1 27400607

eCl@ss 7.1 27400607

ETIM 4.0 EC001166

ETIM 5.0 EC001166

Approvals

Standards

IEC 61439-1:2011

GB/T 7251.1

Approvals

CSA, UL, DNV GL



type number: 485

UL file: E123577, UL category (for USA): NMTR2 <http://www.ul.com>

UL file: E123577, UL category (for Canada): NMTR8 <http://www.ul.com>

CSA file: 110285, CSA class: 3211-37 <http://directories.csa-international.org>

CCC approval: no certification required

Product data

Details IEC

Standards

IEC 61439-1:2011

GB/T 7251.1

Electrical data IEC

rated voltage (IEC) AC: 690 V

rated frequency (IEC): 50 / 60 Hz

rated isolation voltage U_i AC: 1000 V

rated surge voltage U_{imp} : 8 kV

power dissipation of the article:

The power dissipation at a typical load of 80% of the rated current results to 0 W.
(The power dissipation for operation with rated current would be 0 W.)

Kurzschlussfestigkeit:

Siehe Kurzschlussdiagramm im Bereich Download

Details UL

Standards

UL 508

Electrical data UL

rated voltage (UL) AC: 600 V

rated frequency (UL): 50 / 60 Hz

Mechanical data

W x H x D: 20 x 245 x 51

weight: 26.6 kg/100

poles: 3-pole+N


for busbars: 12, 15, 20, 25, 30 x 5, 10

Material properties

Main body: temperature stability 125°C,
self-extinguishing in acc. to UL 94,
creepage resistance CTI 600,
halogen-free

Screws: screw +/- (PZ2), galvanized, chromized

Accessories



01131

end cover

for busbar supports 01357 and 01485 (1x 01131 = 1 left + 1 right cover)