

CONFIGURABLE SAFETY CONTROLLERS

MOSAIC MO4L HC S8

High current output expansion unit.
Output expansion unit with 4 high current safety outputs (PNP 2,0 A per channel, 8 A total), 4 relative inputs for external feedback contacts (EDM) and 8 status output.
Screw terminal blocks.
Compatible: M1-M1S
Certifications:



Technical data:

Family	MOSAIC
Code	1100032
Safety level (SIL / PL)	SIL 3 - SILCL 3 according to IEC 61508 - IEC 62061 / PL e - Cat. 4 according to ISO 13849-1
Connections	Removable terminal blocks, screw contacts
Power supply (VDC)	24 ± 20%
Safety inputs	-
Safety relay outputs	-
Safety outputs	4 single channels or 2 double channels PNP 2,0 A per channel, 8 A total
system MTTFd (ISO 13849-1) years	100
PFHd (IEC 61508)	9,28E-09
CCF (ISO 13849-1)	80%
Degree of protection	IP 20 for housing - IP 2X for terminal block
Storage temperature (°C)	From -20 to +85
Operating temperature (°C)	From -10 to 55
Programmable signalling outputs	8 PNP - 100mA
Test outputs	-
Start/Restart inputs and EDM	4
LED signalling	Input/output status and fault diagnostics
USB input	-
Housing for MCM	-
Connection with MSC BUS	yes
MSC connector provided	yes
Dimensions HxWxD (mm)	108 x 22,5 x 114,5
Fastening	Rail fastening according to EN 50022-35 standard
Packaging dimensions W x H x L (mm)	160 x 135 x 60
Gross weight (Kg)	0,25

Related products:

[MOSAIC CPM](#)

See technical drawing in the next page.

Technical drawing:

