

AD SRE4

Order Code: 1330913

Safety Interface for E-Stops and Safety Switches. Automatic/Manual Restart. Cat. 4. 3 NO + 1 NC contacts



Safety level

PL e

Safety relay outputs

3 NO + 1 NC (5A at 250 VAC)

Technical Description

Safety interface for emergency stop buttons and safety switches monitoring

- Guided-contact safety relays
- EDM Feedback input for external contactors monitoring
- Automatic/Manual Start/Restart
- Can be used up to safety Category 4, PL e according to EN ISO 13849-1

Features

Safety level	PL e
Safety level (SIL / PL)	PL e - Cat. 4
Operating temperature (°C)	- 25 ... 55
Response time (ms)	
Signalling	LEDs indication for status and diagnostic: power supply, channel 1 and channel 2
Connections	Terminal blocks
MTTFD (ISO13849) years	71
Safety devices to be connected	Emergency stop buttons and safety switches
Min. switching current at 24 VDC (mA)	6
Safety relay outputs	3 NO + 1 NC (5A at 250 VAC)
Packaging dimensions HxLxW (mm)	45 x 165 x 110
Product class	C
Custom tariff	85365080

Electrical data

Power supply (VDC)	24 ± 20%
--------------------	----------

Mechanical data

Dimensions HxWxD (mm)	99 x 22,5 x 114
Fastening	35 mm DIN rail fastening according to EN 50270 standard

AD SRE4

Gross weight (g)

220

Certificates

