

383170249024

Relay interface module (EMR or SSR) 0.1 - 2 - 3 - 5 - 6 - 8 - 16 A



This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.

Technical description:

Relay interface modules, timer SSR 14 mm wide, with screw terminal, 5 A, 5 A - 24 V DC, DC input version, nominal voltage 24 V, operating from 16.8 to 30 V, rated power 0.3 W, consumption 12 mA, must drop-out voltage 5 V, ambient temperature from -20 to +55 °C

[BROWSE PRODUCT PAGE](#)

Technical Features:

Ambient temperature range:	-20...55 °C
Commercial Description:	Relay Interface Module with solid state relay, single output, width 14 mm. Equipped with screw terminals. With AC or DC output circuit and DC input circuit. 35 mm rail (EN 60715) mounting. Designed for interfacing with PLC systems
Contact configuration:	1 NO
Dimensions:	14x88.4x73.6 mm
Nominal voltage DC:	24 V
Operating range DC:	16.8...30 V
Rated contact voltage:	24 V DC
Rated current (contacts):	5 A
Rated power DC:	0.3 W
Supply:	DC input version
Certifications and quality approvals (according to type):	     

The information, technical details, data and features contained in this document are subject to change or modification at any time.
It is for information purposes only and does not form the basis of a contract.

Need more information?
[Contact our sales](#) [Find a dealer](#)