


385200240060

Relay interface module (EMR or SSR) 0.1 - 2 - 3 - 5 - 6 - 8 - 16 A










Technical description:

Relay interface modules, Electromechanical relay, with screw terminal, 2 pole, CO (nPDT), 8 A, AgNi, AC/DC coil, 24 V, operating from 19.2 to 26.4 V (AC)/(DC), rated power 0.5 VA (AC)/(DC), consumption 20 mA, holding voltage 14.4 V (AC)/(DC), must drop-out voltage 2.4 V (AC) and 1.2 V (DC), option: AC or AC/DC, ambient temperature from -40 to +70 °C

This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.

[BROWSE PRODUCT PAGE](#)

Technical Features:

Ambient temperature range:	-40...70 °C
Commercial Description:	Relay Interface Modules with screw terminals, (EMR) electromechanical relay, 2 CO 8 A, width 14 mm. Designed for interfacing with PLC systems
Contact configuration:	2 pole, CO (nPDT)
Dimensions:	14x88.4x73.6 mm
Electrical life:	60000 cycles
Insulation coil/contacts:	6 kV
Nominal voltage AC:	24 V
Nominal voltage DC:	24 V
Operating range AC:	19.2...26.4 V
Operating range DC:	19.2...26.4 V
Rated contact voltage:	250 V AC
Rated current (contacts):	8 A
Rated power AC:	0.5 VA
Rated power DC:	0.5 W
Supply:	AC/DC coil
Certifications and quality approvals (according to type):	      

The information, technical details, data and features contained in this document are subject to change or modification at any time. It is for information purposes only and does not form the basis of a contract.

Need more information?

[Contact our sales](#) [Find a dealer](#)