


385202400060

Relay interface module (EMR or SSR) 0.1 - 2 - 3 - 5 - 6 - 8 - 16 A



This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.

Technical description:

Relay interface modules, Electromechanical relay, with screw terminal, 2 pole, CO (nPDT), 8 A, AgNi, DC coil, 220 V, operating from 184 to 264 V, rated power 0.9 W, consumption 3.8 mA, holding voltage 144 V, must drop-out voltage 12 V, option: AC or AC/DC, ambient temperature from -40 to +70 °C

[BROWSE PRODUCT PAGE](#)

Technical Features:

Ambient temperature range:	-40...70 °C
Commercial Description:	Relay Interface Modules with screw terminals, (EMR) electromechanical relay, 2 CO 8 A, width 14 mm. Designed for interfacing with PLC systems
Contact configuration:	2 pole, CO (nPDT)
Dimensions:	14x88.4x73.6 mm
Electrical life:	60000 cycles
Insulation coil/contacts:	6 kV
Nominal voltage DC:	220 V
Operating range DC:	184...264 V
Rated contact voltage:	250 V AC
Rated current (contacts):	8 A
Rated power DC:	0.9 W
Supply:	DC coil
Certifications and quality approvals (according to type):	

The information, technical details, data and features contained in this document are subject to change or modification at any time.
It is for information purposes only and does not form the basis of a contract.

Need more information?
[Contact our sales](#) [Find a dealer](#)