

503.3286

INTERLOCKED SOCKET

32A 3P+E 6h 380-415V II 2D 130X260MM_PAR

With mechanical interlock

Product Approvals



I.M.Q.

Istituto Italiano del Marchio di Qualità



IMQ ATEX

Istituto Italiano del Marchio di Qualità -
Divisione ATEX

EAC

Eurasian Conformity



Notifica ATEX

Product quality assurance notification



UE

Declaration of conformity

TECHDATA

Commercial series	ADVX
Type of product	INTERLOCKED SOCKET
Synthetical description	INTERLOCKED SOCKET
Mounting version	SURFACE MOUNTING
Rated current	32A
Poles	3P+E
Hour position	6h
Rated voltage (range)	250-400V
Rated voltage	380-415V
Colour	RED
Protection degree	Splash proof
Protection degree IP	IP66
Flange	130X260MM_PAR
Group and categories EX	II 2D

STANDARDS AND LAWS

EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
EN 60309-1/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
EN 60309-2/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
EN 60309-4 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock
EN 60309-1/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
EN 60309-2/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements

Dust protection	Ex tb IIIC T90 °C Db IP66		for pin and contact-tube accessories of harmonized configurations
Ambient temperature Ta min	-25 °C	EN 60309-4/A1 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock
Ambient temperature Ta max	60 °C		
Options	With mechanical interlock	EN 60079-0 (2012)	[European Standard] Explosive atmospheres. General requirements.
Padlock	ø5mm	EN 60079-31 (2014)	[European Standard] Explosive atmospheres. Equipment dust ignition protection by enclosure "t"
		EN 60079-0/A11 (2013)	[European Standard] Explosive atmospheres. General requirements.
		DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
		DIRECTIVE EMC 2014 /30/UE	[European Directives] Electromagnetic Compatibility Directive
		DIRECTIVE ATEX 2014/34/UE	[European Directives] Atmosphere Explosive