

551481100000

General purpose relay 7 - 10 A



This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.

Technical description:

Industrial relay, PCB mount, 4 pole, CO (nPDT), 7 A, AgNi, AC coil, 110 V, operating from 88 to 121 V, rated power 1.5 VA, resistance 3940 Ω, consumption 12.5 mA, holding voltage 88 V, must drop-out voltage 22 V, ambient temperature from -40 to +85 °C

[BROWSE PRODUCT PAGE](#)

Technical Features:

Ambient temperature range:	-40...85 °C
Commercial Description:	General purpose PCB relay, 4 CO 7 A. With AC or DC coil. Cadmium-free contacts. Contact material options RT III version (washable) available.
Contact configuration:	4 pole, CO (nPDT)
Dimensions:	20.7x35.8x27.7 mm
Electrical life:	150000 cycles
Insulation coil/contacts:	4 kV
Nominal voltage AC:	110 V
Operating range AC:	88...121 V
Rated contact voltage:	250 V AC
Rated current (contacts):	7 A
Rated power AC:	1.5 VA
Supply:	AC coil
Certifications and quality approvals (according to type):	       

The information, technical details, data and features contained in this document are subject to change or modification at any time.
It is for information purposes only and does not form the basis of a contract.

Need more information?
[Contact our sales](#) [Find a dealer](#)