


623391100040

Power relay 16 A



This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.

Technical description:

High Power relay, Plug-in socket version, 3 pole, CO (nPDT), 16 A, AgCdO, DC coil, 110 V, operating from 88 to 121 V, rated power 1.3 W, resistance 9420 Ω, consumption 11.7 mA, holding voltage 66 V, must drop-out voltage 11 V, option: Lockable test button + mechanical indicator, ambient temperature from -40 to +70 °C

[BROWSE PRODUCT PAGE](#)

Technical Features:

Ambient temperature range:	-40...70 °C
Commercial Description:	16 A power relay, 3 CO or NO contacts (NO contact gap ≥ 3 mm), socket mounting (92 Series) or directly via Faston 187 (4.8 x 0.5 mm). Equipped with AC or DC coil, LED, lockable test button and standard mechanical indicator. Reinforced insulation between coil and contacts according to EN 60335-1; clearance/creepage separation 6/8 mm
Contact configuration:	3 pole, CO (nPDT)
Dimensions:	38.2x49.1x35.8 mm
Electrical life:	100000 cycles
Insulation coil/contacts:	6 kV
Nominal voltage DC:	110 V
Operating range DC:	88...121 V
Rated contact voltage:	250 V AC
Rated current (contacts):	16 A
Rated power DC:	1.3 W
Supply:	DC coil
Certifications and quality approvals (according to type):	      

The information, technical details, data and features contained in this document are subject to change or modification at any time.
It is for information purposes only and does not form the basis of a contract.

Need more information?
[Contact our sales](#) [Find a dealer](#)