


668290240000

Power relay 30 A



This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.

Technical description:

High Power relay, Faston 250 with top flange mount, 2 pole, CO (nPDT), 10 A, AgCdO, DC coil, 24 V, operating from 19.2 to 26.4 V, rated power 1.7 W, resistance 340 Ω , consumption 70.5 mA, holding voltage 12 V, must drop-out voltage 2.4 V, ambient temperature from -40 to +70 °C

[BROWSE PRODUCT PAGE](#)

Technical Features:

Ambient temperature range:	-40...70 °C
Certifications and quality approvals (according to type):	Canadian Standards Association Conformità Europea EurAsian Conformity European Norms Electrical Certification 03 Recognized Component Mark for Canada and United States Registro Italiano Navale UK Conformity Assessed VDE Prüf- und Zertifizierungsinstitut Zeichengenehmigung
Commercial Description:	2 pole changeover (DPDT) 30 A power relay with 250 Faston connections and Flange mount. Variant also available as: -Type 66.82-x30x, 2 Pole NO (DPST-NO), Faston 250 connections and Flange mount -Type 66.82-x60x, 2 Pole NO (DPST-NO), \geq 1.5 mm contact gap, Faston 250 connections and Flange mount
Contact configuration:	2 pole, CO (nPDT)
Dimensions:	33.5x31x68.5 mm
Electrical life:	100000 cycles
Insulation coil/contacts:	6 kV
Nominal voltage DC:	24 V
Operating range DC:	19.2...26.4 V
Rated contact voltage:	250 V AC
Rated current (contacts):	10 A
Rated power DC:	1.7 W
Supply:	DC coil

The information, technical details, data and features contained in this document are subject to change or modification at any time. It is for information purposes only and does not form the basis of a contract.

Need more information?

[Contact our sales](#) [Find a dealer](#)