


682290124300

Power relay






Technical description:

High Power relay, PCB terminals, 1.5 mm gap between PCB and relay base, 2 pole, 2 NO, 100 A, AgSnO₂, DC coil, 12 V, operating from 10.8 to 13.2 V, rated power 2.9 W, resistance 50 Ω, consumption 240 mA, holding voltage 6 V, must drop-out voltage 0.6 V, ambient temperature from -40 to +70 °C

This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.

[BROWSE PRODUCT PAGE](#)

Technical Features:

Ambient temperature range:	-40...70 °C
Commercial Description:	PCB mount power relay 2 NO 100 A for high power applications. Contact gap of 3.6mm. Meets the requirements of EN 60335-1 relating to resistance to heat and fire.
Contact configuration:	2 NO
Dimensions:	52.5x57.5x52.5 mm
Electrical life:	30000 cycles
Nominal voltage DC:	12 V
Operating range DC:	10.8...13.2 V
Rated contact voltage:	400 V AC
Rated current (contacts):	100 A
Rated power DC:	2.9 W
Supply:	DC coil
Certifications and quality approvals (according to type):	  

The information, technical details, data and features contained in this document are subject to change or modification at any time. It is for information purposes only and does not form the basis of a contract.

Need more information?

[Contact our sales](#) [Find a dealer](#)