



DG TT 2P 10 340 SA (900 454)



Figure without obligation



Basic circuit diagram DG TT 2P 10 340 SA



Dimension drawing DG TT 2P 10 340 SA

Modular surge arrester for use in TT and TN systems (1+1 configuration).

Type	DG TT 2P 10 340 SA
Part No.	900 454
SPD according to EN 61643-11 / IEC 61643-11	type 2 / class II
Power supply system	single-phase TT / TN system
Nominal voltage (a.c.) (U _N)	230 V (50 / 60 Hz)
Max. continuous operating voltage (a.c.) [L-N] (U _C)	340 V (50 / 60 Hz)
Max. continuous operating voltage (a.c.) [N-PE] (U _C)	255 V (50 / 60 Hz)
Follow current extinguishing capability [N-PE] (I _{fi})	100 A
Nominal discharge current (8/20 μs) [L-N] (I _n)	10 kA
Nominal discharge current (8/20 μs) [N-PE] (I _n)	10 kA
Max. discharge current (8/20 μs) [L-N] (I _{max})	20 kA
Max. discharge current (8/20 μs) [N-PE] (I _{max})	20 kA
Voltage protection level (U _p)	≤ 1.3 kV
Protective conductor current (I _{PE})	≤ 5 μA
Response time [L-N] (t _A)	≤ 25 ns
Response time [N-PE] (t _A)	≤ 100 ns
Max. mains-side overcurrent protection	125 A gG
Short-circuit withstand capability (I _{SCCR})	25 kA _{rms}
Temporary overvoltage (TOV) [L-N] (U _T) – Characteristic (U _T)	335 V / 5 sec. - withstand
Temporary overvoltage (TOV) [L-N] (U _T) – Characteristic (U _T)	440 V / 120 min. – safe failure
Temporary overvoltage (TOV) [N-PE] (U _T) – Characteristic (U _T)	1200 V / 200 ms. – withstand
Operating temperature range	-40 °C ... +80 °C
Operating state / fault indication	green / red
Number of ports	1
Cross-sectional area, solid / flexible (min.)	2.5 mm ²
Cross-sectional area, solid / flexible (max.)	25 mm ² / 16 mm ²
For mounting on	35 mm DIN rails acc. to EN 60715
Enclosure material	thermoplastic, red, UL 94 V-0
Place of installation	indoor installation
Degree of protection	IP 20
Capacity	2 module(s), DIN 43880
Weight	145 g
GTIN	6942299503210
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.