

Data sheet

Art.No.: 92.030.4853.0

Distributor GST18i3V 3P1 F V WS

Distribution block GST18i3, 3 pole, 1 input, 3 outputs, with mounting option, 250 V, 20 A, colour of coding: white

1011011010001010010101101
0100110110010110100101010
101001101100111001010010
10101001101100111001010010
1101010011011001011010010
101010011011001011010010
10101010010101101010011

DIGITALIZATION IN PROGRESS

Art.No.	92.030.4853.0
EAN	4015573437203
Order Unit	1

Certificates / Approvals



Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Lockable	self-locking (unlocking by tool)
Color of coding/ contact carrier	white
Marking of poles	L, N, PE

Model

Number of inputs	1
Number of outputs	3
Type of fastening	Yes
Degree of protection (IP)	IP20
Type of distributor	H-distributor

Material

Housing material	Polyamide
halogen free	Yes
Contact material	CuZn
Fire load	0.152 kWh
Insulation components continuous temperature	100 °C
Surface finish	Silver-plated

Classification

ECLASS 8.1	27440603
ETIM 7.0	EC002567
ETIM 6.0	EC002567

ETIM 5.0	EC002567
ETIM 4.0	EC002567

Dimensions

Length	44 mm
Width	52 mm
Height	35 mm