

Art.-Nr.: 116054

## Datasheet



K'ELECTRIC GMBH | Carl-Benz-Str. 7 | D-95448 Bayreuth  
Tel.: +49 921 151 26 78-0 | Fax: +49 921 151 26 78-20  
office@k-electric-gmbh.de | www.k-electric-gmbh.de

## Pressure clamps 1,5...70mm<sup>2</sup>, for 5mm bus bars

Bail clamps for copper conductors

**Weight:** 0.050 kg per piece, **Packaging unit (VPE):** 25

approved acc. to

EN 60999-1:2000; EN 60999-2:2003; EN 61439-1:2011  
CE-compliant and meets EU RoHS directives

### Electrical Data according to IEC

Max. operating voltage:  
Max. current load capacity:

1000 V AC / 1500 V DC  
400 A

### Mechanical Data

Clamp bracket material:  
Pressure bracket material:  
Screw material:  
Spring material:  
Connection cross-section:  
Sector conductors:  
Tightening torque:

Steel, zinc-plated  
Steel, zinc-plated  
Steel, zinc-plated  
Spring steel  
10–50 mm<sup>2</sup>  
35–50 mm<sup>2</sup>  
10 Nm

\*Fine-stranded conductors can also be used without ferrules. National standards must be observed!

The specified tightening torques must generally be applied. The deviation from the rated value for screw and clamp connections must not exceed  $\pm 10\%$  unless otherwise specified.



Art.-Nr.: 116054

# Datasheet



K'ELECTRIC GMBH | Carl-Benz-Str. 7 | D-95448 Bayreuth  
Tel.: +49 921 151 26 78-0 | Fax: +49 921 151 26 78-20  
office@k-electric-gmbh.de | www.k-electric-gmbh.de

## Dimensions (in mm)

