

Art.-Nr.: 116064

Datasheet



K'ELECTRIC GMBH | Carl-Benz-Str. 7 | D-95448 Bayreuth
Tel.: +49 921 151 26 78-0 | Fax: +49 921 151 26 78-20
office@k-electric-gmbh.de | www.k-electric-gmbh.de

Pressure clamps 1,5...70mm², for 10mm bus bars

Bail clamps for copper conductors

Weight: 0.050 kg per piece, **Packaging unit (VPE):** 20

approved acc. to

EN 60999-1:2000; EN 60999-2:2003; EN 61439-1:2011
CE-compliant and in conformity with EU RoHS directives



Electrical Data according to IEC

Max. operating voltage:

1000 V AC / 1500 V DC

Max. current load capacity:

400 A

Mechanical Data

Clamp bracket material:

Steel, zinc-plated

Pressure bracket material:

Steel, zinc-plated

Screw material:

Steel, zinc-plated

Spring material:

Spring steel

Connection cross-section:

10–50 mm²

Sector conductors:

35–50 mm²

Tightening torque:

10 Nm

*Fine-stranded conductors can also be used without ferrules. National standards must be observed!

The specified tightening torques must generally be applied. The deviation from the rated value for screw and clamp connections must not exceed $\pm 10\%$ unless otherwise specified.



Art.-Nr.: 116064

Datasheet



K'ELECTRIC GMBH | Carl-Benz-Str. 7 | D-95448 Bayreuth
Tel.: +49 921 151 26 78-0 | Fax: +49 921 151 26 78-20
office@k-electric-gmbh.de | www.k-electric-gmbh.de

Dimensions (in mm)

