



M-CVM-AB-Modbus-TCP (switch)

M-CVM-AB-Modbus-TCP (switch), expansion module

Code: M56E0A.

- > Protocol: Modbus/TCP (gateway to TCP)
- > Memory: No
- > Communications: Ethernet

Specifications

DC power supply

Consumption	2W
-------------	----

Mechanical characteristics

Size (mm) width x height x depth	90 x 90 x 90 (mm)
Envelope	Self-extinguishing V0 plastic
Fastening	Panel
Weight (kg)	0,12

Environmental characteristics

Protection class	IP 30
Relative humidity (without condensation)	5 ... 95%
Storage temperature	-20... +80 °C
Working temperature	-10...+50 °C

Standards

Certifications	UL/CSA 61010-1 3rd edition
Electrical safety, Maximum height (m)	2000
Standards	IEC 61010, UNE-EN 61000-6-2, UNE-EN 61000-6-4, IEC 664, UNE-EN 55022

Communications

Fieldbus (ModBus)	RS-485 (RJ-45 connector)
Protocol	Modbus/TCP
Speed	Ethernet 10 /100 BT (Mbit/s), Modbus: 9600-19200-38400-57600-76800-115200

M-CVM-AB-Modbus-TCP (switch)

CODE	TYPE	Communications	Protocol
M56E0A.	M-CVM-AB-Modbus-TCP (switch)	Ethernet	Modbus/TCP (gateway to TCP)



M-CVM-AB-Modbus-TCP (switch)

Expansion modules M-CVM-AB-Modbus/TCP (switch)

Code: M56E0A.

Dimensions



Connections

