



CCE-A

CCE-A, Transducer Aac

Code: M25111.

- > Output type: 2
- > Analog output: 4...20mA
- > Measure: 5 A
- > Paramètre: A ~

Specifications

AC power supply, insulation

Pulse test (kV)	4 kV (1,2/50µs)
Test voltage (kV)	3 kV RMS 50 Hz 1min

AC power supply

Consumption	2,5 VA
Frequency	40...90 Hz
Nominal voltage	115/230 Vca (-10...+10 %)

DC power supply, insulation

Pulse test (kV)	3 kV (1,2/50µs)
Test voltage (kV)	2 kV RMS 50Hz 1 min

DC power supply

Consumption	2,5 VA
Nominal voltage	9-18 / 18-36 Vdc 36-72 / 90-140 Vdc

Mechanical characteristics

Size (mm) width x height x depth	20 x 70 x 110 (mm)
Weight (kg)	0,15

Environmental characteristics

Protection class	IP 20 (Terminals) IP 40 (case)
Storage temperature	-40....+70 °C
Working temperature	-10...+60 °C

Current measurement circuit

Consumption	0,2 VA
Nominal frequency	45/65 Hz
Nominal current (In)	1 A / 5 A
Phase current measurement	5...120 % In
Allowable overload	300 % In permanent

Standards

Electrical safety, Maximum height (m)	2000
---------------------------------------	------



CCE-A

Narrow section AC Current transducer

Code: M25111.

Standards	IEC 529, IEC 688, IEC 801, EN 50081-1, EN 50082-1, IEC 1010
-----------	---

Analogue inputs	
Load impedance in current	< 500 Ω
Ripple (effective RMS value)	< 2 %
Load impedance in voltage	> 500 Ω
Response time	< 300 ms (0...99 % Vn)

Analogue outputs	
Displaced output	0,2...2 V / 2...10 V / 4...20 mA

Measurement accuracy	
Phase current measurement	0,5 % FS

CCE						
CODE	TYPE	Output type	Analog output	System	Measure	Paramètre
AC Current transducer						
M25111.	CCE-A	2	4...20mA	-	5 A	A ~
M25121.	CCE-A-AP	1, 3	0...20mA	-	5 A	A ~



CCE-A

Narrow section AC Current transducer

Code: M25111.

Dimensions



Connections

