



CLP-C-44/2,5

CLP-C-44/2,5, CLZ Capacitor with circuit breaker and contactor

Code: R22574.

- > IP: 20
- > In (A): 3.28
- > Frequency (Hz): 50
- > kvar (440 V): 2,5
- > Cut off power: 6 kA
- > Use voltage (V): 440
- > Type of protection: Circuit breaker and contactor

Specifications

Electrical characteristics

Permanent overload	1,3 In
Discharge resistance	75 V / 3 min
Surge	10 % 8 h over 24 h 15 % up to 15 min over 24 hours 20 % up to 5 min over 24 hours 30 % up to 1 min over 24 hours
Manoeuvre voltage	Contactors: 230 V
Tolerance C	± 10 %
Insulation voltage, circuit	3 / 15 kV

Mechanical characteristics

Size (mm) width x height x depth	215 x 490 x 147 (mm)
Envelope	RAL 7035 Grey / RAL 3005 Garnet
Fastening	Vertical
Ventilation	Natural
Weight (kg)	1,2

Environmental characteristics

Protection class	IP 21
Relative humidity (without condensation)	80%
Working temperature	T° class D: Daily average: 45 °C, annual average: 35 °C, maximum: 50 °C, minimum: -25 °C

Standards

Certifications	VDE 560
Electrical safety, Maximum height (m)	2000
Standards	IEC 60831-1, IEC 70/7, UNE-EN 20827, UNE-EN 20010, BS 1650

Features / performance

Components	CS capacitor Protection at the header by high cut-off power circuit breaker (APR)
------------	---

CLP-C



CLP-C-44/2,5

CLZ capacitor with circuit breaker and contactor

Code: R22574.

CODE	TYPE	kvar (440 V)	Use voltage (V)
440 Vac / 50Hz			
R22574.	CLP-C-44/2,5	2,5	440
R22575.	CLP-C-44/3	3	440
R22578.	CLP-C-44/5	5	440
R22579.	CLP-C-44/6,25	6,25	440
R2257A.	CLP-C-44/7,5	7,5	440
R2257C.	CLP-C-44/10	10	440
R2257D.	CLP-C-44/12,5	12,5	440
R2257E.	CLP-C-44/15	15	440
R2257F.	CLP-C-44/20	20	440
R2257G.	CLP-C-44/25	25	440



CLP-C-44/2,5

CLZ capacitor with circuit breaker and contactor

Code: R22574.

Dimensions

