



CLP-44/2,5

CLP-44/2,5, CLZ Power capacitor with circuit breaker

Code: R21574.

- > IP: 20
- > In (A): 3.28
- > Frequency (Hz): 50
- > kvar (440 V): 2,5
- > Cut off power: 6 kA
- > Use voltage (V): 440
- > Type of protection: Circuit breaker

Specifications

Electrical characteristics

Permanent overload	1,3 In
Discharge resistance	75 V / 3 min
Surge	10 % 8 h over 24 h 15 % up to 15 min over 24 hours 20 % up to 5 min over 24 hours 30 % up to 1 min over 24 hours
Manoeuvre voltage	Contactors: 230 V
Tolerance C	± 10 %
Insulation voltage, circuit	3 / 15 kV

Mechanical characteristics

Size (mm) width x height x depth	80 x 350 x 85 (mm)
Envelope	RAL 7035 Grey / RAL 3005 Garnet
Fastening	Vertical
Ventilation	Natural
Weight (kg)	1,2

Environmental characteristics

Protection class	IP 21
Relative humidity (without condensation)	80%
Working temperature	T° class D: Daily average: 45 °C, annual average: 35 °C, maximum: 50 °C, minimum: -25 °C

Standards

Certifications	VDE 560
Electrical safety, Maximum height (m)	2000
Standards	IEC 60831-1, IEC 70/7, UNE-EN 20827, UNE-EN 20010, BS 1650

Features / performance

Components	CS capacitor Protection at the header by high cut-off power circuit breaker (APR)
------------	---

CLP



CLP-44/2,5

Power capacitor with circuit breaker

Code: R21574.

CODE	TYPE	kvar (440 V)	Use voltage (V)
440 Vac / 50Hz			
R21574.	CLP-44/2,5	2,5	440
R21575.	CLP-44/3	3	440
R21578.	CLP-44/5	5	440
R21579.	CLP-44/6,25	6,25	440



CLP-44/2,5

Power capacitor with circuit breaker

Code: R21574.

Dimensions

