



Kit3-CPG-2000/200

Kit3-CPG-2000/200, Clamp

Code: M810C5.

- > Nr Sensors: 3
- > Useful diam.(mm): 64
- > Measurement Range (A): 1 ... 200 A / 10 ... 2000 A
- > I min.(A): 1 | 10

Specifications

Specific technical characteristics of current sensors

Measurement range	1...200 Ac.a. / 10...2000 Ac.a.
Dielectric rigidity	5200 V, 50 Hz, 1 min.
Output voltage	2 Vc.a.

Current measurement circuit

Nominal frequency	48...65 Hz
Tolerance	ESCALA DE 200: 1...3A (0,5% + 70mV) Fase: NC / 3...10A (0,5% + 70mV) Fase: 5 ° / 10...50A (0,5% + 70mV) Fase: 1,5 ° / 50...200A (0,5% + 70mA) Fase: 1 ° ESCALA DE 2000: 10...150A (0,5% + 250mA) Fase: NC / 150...2000A (0,5% + 100mA) Fase: 0,5 °

Mechanical characteristics

Weight (kg)	1
-------------	---

CPG

CODE	TYPE	Measurement Range (A)	I min.(A)	Useful diam.(mm)	Flat strip(mm)
M810B1.	CPG-5	0,05 ... 5 A	0.05	20	20 x 5
M810C1.	Kit3-CPG-5	0,05 ... 5 A	0.05	20	20 x 5
M810D1.	Kit4-CPG-5	0,05 ... 5 A	0.05	20	20 x 5
M810B2.	CPG-100	1 ... 100 A	1	20	20 x 5
M810C2.	Kit3-CPG-100	1 ... 100 A	1	20	20 x 5
M810D2.	Kit4-CPG-100	1 ... 100 A	1	20	20 x 5
M810B3.	CPRG-500	1 ... 500 A	1	52	1 - 50 x 5 4 - 30 x 5
M810C3.	Kit3-CPRG-500	1 ... 500 A	1	52	1 - 50 x 5 4 - 30 x 5
M810D3.	Kit4-CPRG-500	1 ... 500 A	1	52	1 - 50 x 5 4 - 30 x 5
M810B4.	CPRG-1000	1 ... 1000 A	1	52	1 - 50 x 5 4 - 30 x 5
M810C4.	Kit3-CPRG-1000	1 ... 1000 A	1	52	1 - 50 x 5 4 - 30 x 5
M810D4.	Kit4-CPRG-1000	1 ... 1000 A	1	52	1 - 50 x 5 4 - 30 x 5
M810B5.	CPG-2000/200	1 ... 200 A / 10 ... 2000 A	1 10	64	5 - 125 x 5 3 -100 x 10
M810C5.	Kit3-CPG-2000/200	1 ... 200 A / 10 ... 2000 A	1 10	64	5 - 125 x 5 3 -100 x 10
M810D5.	Kit4-CPG-2000/200	1 ... 200 A / 10 ... 2000 A	1 10	64	5 - 125 x 5 3 -100 x 10
M810BD.	CFG-5	0,01 ... 5 A	0.01	52	1 - 50 x 5 4 - 30 x 5



Kit3-CPG-2000/200

Current sensors for portable power analyzers

Code: M810C5.

CODE	TYPE	Measurement Range (A)	I min.(A)	Useful diam.(mm)	Flat strip(mm)
M810BE.	CFG-10	0,005 ... 10 A	0.05	100	5 - 80 x 5 3 -80 x 10