



1-pole, 32A Modular Switch

Reference: SBN132
 EAN Code: 3250615510129
 Pack quantity: 1 Part
 Product price list: To be defined

Description

Technical information	Values
Acceptable current rating with AC22 category A	32 A
Connection cross-sect. flexible cable	1,5 / 10mm ²
Connection cross-sect. rigid cable	1,5 / 16mm ²
Connection type (text)	With screw
Depth of installed product	68 mm
Device family	SBN
Frequency	50/60 Hz
Hager installation time	90 s
Hager wiring time	225 s
Height of installed product	83 mm
Indicator lamp	no
Installation time	90 s
Net weight of the product	58 g
Number of changeover switch contacts	0
Number of half-modules for the labelling field	2 ½ Mod
Number of mechanical operations	200000
Number of modules	1
Number of NC contacts	0
Number of NO contacts	1
Number of poles	1 P
Number of products in the packaging	1
Product group number for calculating the heating processes	1
Protection index IP	IP20

SBN132

Technical information	Values
Quantity of half modules of 17,7mm	2 ½ Mod
Rated current	32 A
Rated impulse withstand voltage	4000 V
Rated insulation voltage	440 V
Rated operating current, AC22	32 A
Rated operational voltage Ue	230 V
Rated short-circuit making capacity Icm (kA peak) at 230V following IEC 60947-2	677 A
Short-circuit current with gl-gG fuses	480 A
Tightening torque	1,8Nm
Total power loss under IN	1.5 W
Type of order	Load switch
Type of pole	1P
Width of installed product	18 mm
Wiring time	225 s