

Information sheet

ST314



Safety transformer 40VA 230V12-24V

Reference: ST314
 EAN Code: 3250615703149
 Pack quantity: 1 Part
 Product price list: To be defined

Description

Technical information	Values
Connection cross-sect. flexible cable	4mm ²
Connection cross-sect. rigid cable	6 mm ²
Copper weight of the product	178 g
Depth of installed product	58 mm
Device family	ST
Fixing type	Din-Rail
Frequency	50 Hz
Hager installation time	200 s
Hager wiring time	360 s
Height of installed product	85 mm
Installation time	200 s
Length	70 mm
Net weight of the product	846 g
Number of half-modules for the labelling field	0 ½ Mod
Number of modules	4
Number of products in the packaging	1
Operating temperature	-20 °C to 35 °C
Power consumed	40 VA
Power in VA	40 VA
Primary/secondary voltage	230 V AC / 12 - 24 V AC
Product group number for calculating the heating processes	4
Protection index IP	IP20
Quantity of half modules of 17,7mm	8 ½ Mod

ST314

Technical information	Values
Rated insulation voltage	4000 V
Secondary no-load voltage	14.3 V; 27.5 V
Secondary operating voltage	12 V; 24 V
Total power loss under IN	2.1 W
U primary	230 V AC
U secondary	12 - 24 V AC
Width of installed product	70 mm
Wiring time	360 s